

541,890

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/063623 A1

(51) International Patent Classification⁷: **F17D 5/06, 5/02**

(21) International Application Number:
PCT/CA2004/000008

(22) International Filing Date: 13 January 2004 (13.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2,416,171 13 January 2003 (13.01.2003) CA

(71) Applicant (for all designated States except US): **PURE TECHNOLOGIES LTD.** [CA/CA]; 3rd Floor, 705 - 11th Avenue S.w., Calgary, Alberta T2R 0E3 (CA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **PAULSON, Peter, O.** [CA/CA]; 320 Pumphill Gardens S.w., Calgary, Alberta T2V 4M7 (CA).


(74) Agent: **BLAKE, CASSELS & GRAYDON LLP**; World Exchange Plaza, 20th Floor, 45 O'Connor Street, Ottawa, Ontario K1P 1A4 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PIPELINE MONITORING SYSTEM



(57) Abstract: Process and apparatus for sensing possible leaks in a pipeline. The pipeline is monitored continuously by acoustic monitoring means, and acoustic events indicating a possible leak are noted. The pipeline is also equipped with temperature monitoring means, and is monitored for temperature either continuously, periodically or on demand. A leak is deemed probable at any location where there is an acoustic event indicating a possible leak, and at approximately the same time, a temperature difference greater than a pre-chosen amount between that location and adjacent locations

WO 2004/063623 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.